

T E C H N I C A L D A T A S H E E T

Performance Characteristics

Property	Typical Value	Test Method*
Particles and Fibers LPC: ≥0.5 µm Fibers: >100 µm	8.4 x 10 ⁶ particles/m ² 2,000 fibers/m ²	1, TM22 2, TM22
Nonvolatile Residue IPA extractant DIW extractant	0.06 g/m ² 0.01 g/m ²	1, TM1 1, TM1
Ions Sodium Potassium Chloride	0.15 ppm 0.03 ppm 0.10 ppm	1, TM18 1, TM18 1, TM18

Physical Characteristics

Property	Typical Value	Test Method*
Absorbency Sorbent capacity Sorbent rate	530 mL/m ² <0.3 seconds	1, TM20 1, TM20
Basis Weight	158 g/m ²	1, TM20

***Test Methods**

- 1 – “Evaluating Wiping Materials Used in Cleanroom and Other Controlled Environments,” IEST-RP-CC004.3, Institute for Environmental Sciences and Technology, Rolling Meadows, IL, 2004; www.iest.org.
- 2 – E2090-12, “Standard Test Method for Size-Differentiated Counting of Particles and Fibers Released from Cleanroom Wipers Using Optical and Scanning Electron Microscopy,” ASTM International, West Conshohocken, PA, 2012; www.astm.org.
- TM – Refers to Texwipe Test Method – available upon request. Contact Texwipe Customer Service at www.texwipe.com or info@texwipe.com for a copy.

Note: The data in this table represent typical analyses.

For non-sterile products:

- TX1034, TX1036, TX1039 – filled using USP grade IPA.

For sterile products:

- Irradiated to a Sterility Assurance Level of 10⁻⁶ according to AAMI Guidelines.
- Certificates of Compliance, Analysis and Irradiation attached to each case.
- Sterile Validation Documentation available upon request.
- STX1034 – filled using USP grade IPA.

Texwipe holds ISO 9001:2015 registrations.

All Texwipe products conform to GHS classification for labeling (where applicable).

Shipping classification based on weight of inner package.

AlphaWipe®

Dry | Pre-Wetted | Sterile

TECHNICAL DATA SHEET



AlphaWipe®
100% Polyester

Products

Number	Description	Sterile	Packaging	Case
<i>Dry Wipers – AlphaWipe®</i>				
SXT1004	4" x 4" (10 cm x 10 cm) dry, sterile	●	50 wipers/bag	50 bags
TX1004	4" x 4" (10 cm x 10 cm) dry		300 wipers/bag (2 bags of 150 wipers)	20 bags
TX1009	9" x 9" (23 cm x 23 cm) dry		150 wipers/bag (2 bags of 75 wipers)	10 bags
TX1009B	9" x 9" (23 cm x 23 cm) dry		150 wipers/bag (2 bags of 75 wipers)	10 bags
TX3211	9" x 9" (23 cm x 23 cm) dry, SterileWipe® LP	●	100 wipers/bag (10 bags of 10 wipers)	5 bags
TX1013	12" x 12" (31 cm x 31 cm) dry		75 wipers/bag double bagged	10 bags
TX1025	24" x 44" (61 cm x 112 cm) dry		25 wipers/bag	3 bags
<i>Pre-Wetted Wipers – AlphaSat®</i>				
STX1034	4" x 4" (10 cm x 10 cm) pre-wetted with 70% IPA, sterile	●	50 wipers/reclosable bag	8 bags
TX1034	4" x 4" (10 cm x 10 cm) pre-wetted with 70% IPA		200 wipers/reclosable bag	4 bags
TX1036	6" x 6" (15 cm x 15 cm) pre-wetted with 70% IPA		75 wipers/reclosable bag	12 bags
TX1039	9" x 9" (23 cm x 23 cm) pre-wetted with 70% IPA		50 wipers/reclosable bag	4 bags

TECHNICAL DATA SHEET

Description

AlphaWipe® is made from 100% polyester material with a cut edge, cleanroom laundered.

Available dry (AlphaWipe®), pre-wetted (AlphaSat®), and sterile.

Applications

- Wiping and cleaning surfaces, equipment and parts.
- Spill control.
- Applying and removing lubricants, adhesives, residues and other solutions including disinfectants.
- Cleaning with solvents such as isopropyl alcohol (IPA), acetone, and degreasers.
- Cleaning gloves, notebooks, phones or any other item entering the cleanroom.
- Lining trays for holding, protecting, drying and storing of parts, equipment and devices.
- Appropriate for use with temperatures less than 400°F (205°C).

Features & Benefits

- Constructed from 100% polyester creating a high absorbency wiper ideal for spill control, cleaning, and solution application.
- Cleanroom laundered and packaged providing ultra low levels of ions and non volatile residues.
- Designed for use on abrasive surfaces. This wiper will not easily snag or abrade releasing particles and fibers into the process or environment.
- Excellent chemical resistance for compatibility with a variety of solutions.
- Meets USP <797> and USP <800> wiper requirements.
- Autoclave safe (dry wipe).
- AlphaSat® products are pre-wet with 0.2 µm filtered 70% IPA / 30% DIW or 6% IPA / 94% DIW for ease of use
- AlphaSat® wipers provide a consistent, optimized cleaning efficiency with repeatable wetness VOC levels.
- AlphaSat® pre-wetted wipers are packaged in easy-to-use, recloseable slider bags, reducing solution evaporation that preserves the consistent wiper wetness level.
- Individually lot coded for ease of traceability and quality control.

Industries

Aerospace	Animal Laboratory	Biologics
Cleanroom Design/Build	Compounding Pharmacies	Data Storage
Facilities Maintenance	Industrial	Laboratory
Medical Device	Microelectronics	Pharmaceutical
Printing/Graphics	Semiconductor	USP <797> / USP <800>

Cleanroom Environment

- ISO Class 4 – 8
- Class 10 – 100,000
- EU Grade A – D

Shelf Life

- Non-Sterile (Dry) – 5 years from date of manufacture
- Non-Sterile (Pre-Wetted) – 3 years from date of manufacture
- Sterile (Dry & Pre-Wetted) – 3 years from the date of manufacture